

CLAIM AMENDMENTS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A method of configuring a data network, the method comprising:
determining an average peak bandwidth per user value for the data network;
determining a capacity of a communication link connecting a digital subscriber line
access multiplexer (DSLAM) and an asynchronous transfer mode (ATM) switch;
determining a data transmission slowdown indicator that includes a slowdown amount
and a probability of experiencing a slowdown event;
determining an estimated maximum number of users of digital subscriber lines that may
be supported by the DSLAM, where the estimated maximum number of users of
digital subscriber lines is based on the average peak bandwidth per user value, the
capacity of the communication link, and the customer data transmission
slowdown indicator; and
configuring the data network such that the DSLAM has a configured number of users of
digital subscriber lines that is less than or equal to the estimated maximum
number of users of digital subscriber lines.
2. (Original) The method of claim 1, wherein the estimated maximum number of users of
digital subscriber lines is further based on a probability of a random user downloading data at a
given period of time.
3. (Original) The method of claim 1, wherein the estimated maximum number of users of
digital subscriber lines is further based on an Erlang model calculation.
4. (Currently amended) The method of claim 1, wherein the communication link is one
or more DS3-Digital Signal-level 3 (DS3) type communication links or an OC3-Optical Carrier-
level 3 (OC3) type communication link.

5. (Currently amended) The method of claim 1, wherein the estimated maximum number of users of digital subscriber lines is calculated with an assumption ~~that a plurality of different users download data at the same data transfer speed of a data transfer speed associated with a~~ plurality of users.

6. (Original) The method of claim 5, wherein the data transfer speed is about 1.5 Mbits/second.

7. (Currently amended) A method of configuring a data network, the method comprising:
determining an average peak bandwidth per user value for the data network;
determining a capacity of a communication link connecting a remote terminal (RT)
to asynchronous transfer mode (ATM) switch via an optical concentrator device;
determining a data transmission slowdown indicator that includes a slowdown amount
and a probability of experiencing a slowdown event;
determining an estimated maximum number of users that may be supported by the RT,
where the estimated maximum number of users is based on the average peak
bandwidth per user value, the capacity of the communication link, and the
~~customer~~-data transmission slowdown indicator; and
configuring the data network such that the RT has a configured number of users of the
subscriber lines that is less than or equal to the estimated maximum number of
users that may be supported by the RT.

8. (Original) The method of claim 7, wherein the communication link comprises a plurality of T1 transmission lines.

9. (Currently amended) The method of claim 7, wherein the communication link comprises one of an ~~OC3~~-Optical Carrier-level 3 (OC3) and one or more ~~DS3~~Digital Signal-level 3 (DS3) links.

10. (Original) A data communications system comprising:
a plurality of digital subscriber lines;
a digital subscriber line multiplexer coupled to each of the plurality of digital subscriber lines; and
a data switch coupled to the digital subscriber line multiplexer via a communication link;
wherein the data communications system is configured such that the number of digital subscriber line users supported by the digital subscriber line multiplexer is determined based on an estimated maximum number of users, the estimated maximum number of users determined based on an average peak bandwidth per user value, a data communication capacity of the communication link, and a data transmission slowdown indicator.

11. (Original) A data communications system comprising:
a plurality of digital subscriber lines;
a remote terminal device coupled to each of the plurality of digital subscriber lines; and
a data switch coupled to the remote terminal device via a communication link;
wherein the data communications system is configured such that the number of digital subscriber line users supported by the remote terminal device is determined based on an estimated maximum number of users, the estimated maximum number of users determined based on an average peak bandwidth per user value, a data communication capacity of the communication link, and a data transmission slowdown indicator.

12. (Original) The system of claim 11, wherein the estimated maximum number of users of digital subscriber lines is further based on a probability of a random user downloading data at a given period of time.

13. (Original) The system of claim 11, wherein the estimated maximum number of users of digital subscriber lines is further based on an Erlang model calculation.

14. (Currently amended) The system of claim 11, wherein the communication link is one or more ~~DS3-Digital Signal-level 3 (DS3)~~ type communication links, an ~~OC3-Optical Communication Level 3 (OC3)~~ type communication link, or one or more T1 type communication links.

15. (Currently amended) The system of claim 11, wherein the estimated maximum number of users of digital subscriber lines is calculated with an assumption ~~that a plurality of different users download data at the same data transfer speed~~ of a data transfer speed associated with a plurality of users.

16. (Original) The system of claim 15, wherein the data transfer speed is about 1.5 Mbits/second.